

MAGNETIC DRILL SPECIFICATIONS

COMMANDO MAG DRILLS

Perfect for on-site drilling solutions or workshop projects, the Commando Range gives maximum performance for a fantastic value.

Model	Cutter Capacity (mm)	Cutter Depth (mm)	Drill Chuck Capacity (mm)	Motor Power (w)	Weight (kg)	Height (mm)	Stroke (mm)	Countersink (mm)	Internal Cable	Interchangable Handle	CutSmart™	Overload Protection	Internal Cooling	Tapping
COMMANDO 35	35	50	13	1050	12	435	105	n/a	✗	✗	✗	✓	✓	✗
COMMANDO 40	40	50	13	1100	14	510	85	30	✗	✗	✗	✓	✓	✗

ELEMENT MAG DRILLS

With intuitive CutSmart™ technology, variable speed options, magnetic detection for easy adhesion and fixed guard, Element Magnetic Drills give you the POWER to cut metal.

Model	Cutter Capacity (mm)	Cutter Depth (mm)	Drill Chuck Capacity (mm)	Motor Power (w)	Weight (kg)	Height (mm)	Stroke (mm)	Countersink (mm)	Internal Cable	Interchangable Handle	CutSmart™	Overload Protection	Internal Cooling	Tapping
ELEMENT 30	32	35	13	850	12	414	65	n/a	✓	✓	✓	✓	✓	✗
ELEMENT 40	40	50	13	1200	13	514	80	n/a	✓	✓	✓	✓	✓	✗
ELEMENT 50	50	50	13	1500	15	586	140	30	✓	✓	✓	✓	✓	✓
ELEMENT 50 PIVOT	50	50	13	1500	18	4640	150	31	✓	✓	✓	✓	✓	✓
ELEMENT 50 LP	50	50	n/a	1200	11	179	62	30*	✓	✓	✓	✓	✓	✗
ELEMENT 75	75	75	13	1800	23	713	185	40	✓	✓	✓	✓	✓	✓
ELEMENT 100	100	100	13	2000	25	733	200	40	✓	✓	✓	✓	✓	✓

*Requires an extension arbor RD32059.